

Architectural Specifications

SPECIFICATIONS – Bird Jolt FlatTrack BIRD ABATEMENT SYSTEM

PART 1 – GENERAL

1.1 SUMMARY

- A. Description of work: Work for this section includes, but is not limited to the following:
 1. Electrified track bird deterrent system.
 2. Control devices and associated wiring and connections for the work of this section.

1.2 QUALITY ASSURANCE

- A. Single Source Responsibility: Furnish products from one manufacturer for the entire project.
- B. Obtain all technical information from the manufacturer.
- C. Utilize labor or Bird-B-Gone Authorized Installers who are certified in Bird-B-Gone product installations. Proof of Certification is required.
- D. Installer shall visit the site to gather all information of existing site conditions.

1.3 SUBMITTALS

- A. Submit all descriptive information for the manufacturer including catalogs, installation instructions and other descriptive material.
- B. Provide Warranty on material and installation.
- C. Provide samples of each type of hardware, including proposed fastening methods.
- D. Provide statement by official indicating that they are a Certified Installation Company.

1.4 SYSTEM REQUIREMENTS

- A. Electrical Requirements:
 1. Provide wiring in accordance with applicable local codes and National Electric Code Standard.
 2. Test wiring system for insulation to ground.

1.5 PRODUCT HANDLING

- A. Protect Bird-B-Gone products from damage before, during and after the installation.
- B. If damage occurs to any Bird-B-Gone Products, make all necessary replacements immediately.

1.6 PROJECT CONDITIONS

- A. Coordination: Furnish samples of system so installation can be coordinated with existing conditions and within on-site tolerances.
- B. Visit site and field-measure prior to fabrication and delivery of materials.
 1. Verify conditions including offsets and other dimensions.

PART 2 – PRODUCTS

2.1 ACCEPTABLE MANUFACTURER

- A. Manufacturer:
Bird-B-Gone, Inc.
Bird Jolt FlatTrack Bird Abatement System (Patent Pending)
23918 Skyline
Mission Viejo, CA 92692

2.2 PRODUCT DESCRIPTION

- A. Model Designation:
 1. Bird Jolt FlatTrack – Electric Bird Abatement System
 - a. Height: 1/4" at the highest point.
 - b. Width: 1-1/2".
 - c. Features:
 - i. Two (2) Stainless Steel Braided Wire Strips 1/4" wide sewn into top of track.
 - ii. Two (2) Glue Troughs running on bottom of strip for easy installation and maximum adhesion.
 - d. Base Strip: Flexible - Can bend 360° on vertical plane.
 - e. Length: 100 ft. rolls.
 - f. Packaging: 100 ft. kits with all installation hardware needed.
 - g. Color: Available in Gray, Stone, Black, or Terracotta.
 - i. As designated by the product specifications.
 - h. Number of rows as determined by the manufacturer and based on project conditions.
 - i. Mounting Systems: As determined by the manufacturer and based on project conditions.

2.3 MATERIALS

- A. Bird Jolt FlatTrack System Kit Components:
 1. Flexible U.V. Stabilized PVC base with stainless steel braided wires sewn into base strip.
 - a. 100 ft. rolls.
 2. U.V. Protected Polycarbonate Mounting Clips.
 - a. 30 per 100 ft. installation.
 3. Bilingual Warning labels.
 - a. 10 per 100 ft. installation.
 4. Power terminal connectors.
 - a. 2 per 100 ft. installation kit.
 5. Insulated lead-in wire.
 - a. 20 ft. per 100 ft. installation kit.
 6. Snug Tight Connectors
 - a. 4 per 100 ft. installation kit.
- B. Bird Jolt FlatTrack Charger System Options:
 1. BJFT-AC750:
 - a. Bird Jolt FlatTrack Direct Charge:Housed in NEMA Type 4 or 3 weatherproof enclosure.
Input Voltage: 110-120 VAC, 60 Hz, .035 amp, 10W.
Output Voltage: 1.2Kv (+/-) 20% open circuit voltage intermittent AC Current.
 2. BJFT-SLR740
 - a. Bird Jolt FlatTrack Solar Charger: **Input Voltage:** 4VDC
Output Voltage: 8Kv (+/-) 20% output pulse width 50uS, output at 100 ohms 3.5A.

- C. Construction:
 1. Bird Jolt FlatTrack: Flexible one-piece construction.
 2. Installation Hardware: Highest quality stainless steel, plastic and metal components.
- D. Adaptation: Sharp Scissors, Exact-O Knife, Cable Cutters, etc. can be used to cut/ adapt the product to desired section length.

2.4 MOUNTING SYSTEMS

- A. Steel, Brick, Stone or Concrete: Attach Bird Jolt FlatTrack Mounting Brackets and Bird Jolt FlatTrack using an outdoor construction adhesive that is non-silicone based. Purchase directly from the manufacturer or call for recommended adhesives.

PART 3 – EXECUTION

3.1 EXAMINATION

- A. Examine the installation area and note any detrimental or hazardous work conditions. Notify contracting officer or inspector of the detrimental work conditions.
- B. Do not proceed with the installation until conditions are corrected.

3.2 SURFACE PREPARATION

- A. Surface should be thoroughly cleaned and free of bird droppings, nesting materials, rust, peeling paint or other debris.
- B. Remove or repair articles that may damage Bird Jolt FlatTrack Electric Bird Abatement System including overhanging foliage, brush and loose parts on the structure.

3.3 INSTALLATION

- A. Install Bird Jolt FlatTrack Electric Bird Abatement System.
 1. Install with appropriate anchors or fasteners for each substrate.
 - a. Glue and Snap-fit the FlatTrack down into each mounting clip.
 - b. Glue remaining track (between mounting clips).
 - c. All FlatTrack strips should be adhered (glued or secured) to surface area being treated.
 2. Space materials in accordance with the manufacturer's recommendations.
 - a. Follow angles and contours closely.
 3. Install bilingual warning labels near power source and no more than 10' apart on buildings, and on windows where electrified wire is on outside ledge.

3.4 INSPECTION

- A. Upon completion of installation, test operation to demonstrate satisfactory operation and acceptability.
- B. Visually inspect Bird Jolt FlatTrack Bird Abatement System for any signs of poor installation, including loose screws, fasteners or un-removed debris.
- C. Immediately correct and repair as necessary.

END OF SPECIFICATIONS